



Brass Prong Snap

HISANAGA

Yotsukaido Industrial Park 598
 Monoi, Yotsukaido-shi Chiba 284-0012 JAPAN
 Tel +81(43)422 2112 · Fax +81(43)423 7147
 overseas.crown@hisanaga-ss.co.jp

B703 Series

Meets the safety, design and reliability requirements of major buyers.


[Usage] Suitable general garments, especially for knitting and baby clothes.

TOP PARTS


PRONG



B703A / LA
(5nails)



B703A / LA
(6nails)



other combination



25A / 10mm




Poly / 10mm
(5nails)

FABRIC

SOCKET



B703B



Combination of Top parts & Socket

Regular prong

Basic pinch	2.50mm
Max attached height	2.85mm
Holding strength	over 9.20kg

Long prong

Basic pinch	2.80mm
Max attached height	3.20mm
Holding strength	over 9.20kg


Closing snap action 3.0 ~ 4.5kg

Opening snap action 0.9 ~ 1.4kg


STUD



B706CW



B703C



Combination of Under parts & Stud

	Regular prong	Long prong
Basic pinch	2.50mm	2.80mm
Max attached height	2.85mm	3.20mm
Holding strength	over 9.20kg	

Combination of Under parts & Post

Basic pinch	1.30mm
Max attached height	2.20mm
Holding strength	over 9.20kg


UNDER PARTS (3PARTS)

FABRIC


PRONG



B703A / LA
(5nails)



B703A / LA
(6nails)



POST



B703D

